



# HYDROTAP G5 BC100 CLASSIC CHROME



BOILING



CHILLED

FILTERED

## Order Code H51705Z00AU

Zip HydroTap Boiling, Chilled, Filtered water system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including 2 boiling water safety modes, 3 energy saving modes including ON/OFF timers and sensor activated 'sleep when it's dark', 'Quiet' mode with automated intelligent fan speed adjustment, SteriTouch® antimicrobial protection impregnated into key water paths for enhanced hygiene, 100% water efficient air cooled technology, and 0.2 micron water filtration. Easy to install integrated ventilation tray included.



Manufacturing Code H51705Z00AU

Capacity Commercial

Boiling Cups per hour 240

Chilled Cups per hour 175

Tap Zip HydroTap CLASSIC Tap (Chrome)

Water Pressure Min 200kPa - Max 700kPa

Water Connection 1/2" BSP (G1/2)

Water Supply Requirements Cold

Water Valves Integrated 500kPa Pressure limiting valve and Dual Check Valve

Power Rating 2.1kW 220-240V 50Hz

Booster Power Rating Zip HydroTap Booster 2.2kW 220-240V 50/60Hz



<b>Power Supply</b>	2 x 10 Amp socket outlets
<b>Dimensions</b>	W395mm x D464mm x H333mm
<b>Product Approvals</b>	WaterMark, RCM, ARC
<b>Warranty</b>	5 years (appliance warranty 36 months plus additional 24 months tank warranty)

## Installation Requirements

1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations. 2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product. 3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation. 4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service. 5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit. 6. Installation by Zip Professional Service can be arranged with a phone call or through [www.zipwater.com](http://www.zipwater.com)

## Installation Detail

BK12 HydroTap G5 v1.01 03.21 BC40 BC60

Ventilation requirements <small>Contact your local service provider if ventilation is not suitable</small>	HydroTap Tap options	Font options
<p><b>Clearance envelope</b> Position the Tap and the Command Centre as close together as possible.</p> <p><b>Vent tray (kit no. 93540)</b></p>	<p><b>Classic Plus</b> <b>Classic</b> <b>Elite Plus</b></p> <p><b>Touch-Free Wave</b></p> <p>100mm clearance envelope required. For Sink installations, install on the left-hand side of the Sink for ease of access to Boiling water function.</p>	<p><b>Raised Font with 135mm Extension</b> part no. 95258</p> <p><b>Font with 135mm Extension</b> part no. 90915</p>
<p><b>Detail A. Air inlet grille</b> Cut-out in cabinet floor</p> <p><b>Detail B. Vent Tray air outlet</b> Cut-out in cabinet floor</p>	<p><b>Tap Positioning</b> Position the Tap to dispense into the sink, allowing clearance for a cup or teapot. Alternatively, mount the HydroTap Tap on a Font (available as an accessory).</p> <p>Ø35mm hole for HydroTap Tap</p>	<p><b>Cutting detail</b></p> <p><b>Cutting detail</b></p>
<p><b>4mm buffer pad air space</b></p>		
<p><b>Classic Plus Tap</b></p> <p><b>Clearance Envelope</b></p> <p><b>Booster (BC100 models)</b> Note: The 500mm braided hoses supplied cannot be lengthened</p> <p><b>IEC Flex &amp; Plug</b> 230-240V, 50Hz power outlet</p> <p><b>Air Inlet</b></p> <p><b>Vent tray</b> Note: should not be impeded by pipework</p> <p><b>Mains cold water isolation valve</b> (not supplied)</p>		

SCALE 1:5  
ALL DIMENSIONS IN MM UNLESS OTHERWISE SPECIFIED. INSTALLATION DIAGRAMS ARE FOR ILLUSTRATIVE PURPOSES ONLY. HOSES ARE NOT SHOWN TO SCALE AND CANNOT BE LENGTHENED.

**HydroTap G5**  
**BC40, BC60, BC100**

shown with "Classic Plus" Tap



